

	SCHEDE TECNICHE / TECHNICAL SPECIFICATIONS	ST138	Autore DST
	NOW 4 LEGS STOOL	Rev. 01	Data 22/03/18



Caratteristiche struttura <i>Frame Specs</i>	<ul style="list-style-type: none"> • Struttura in tubo tondo D.18 sp.2mm Uni En 10305-3:2016. • Anello poggiapiedi in tondino D.11 FE360 • <i>Round tube diameter 18 mm, thickness 2 mm, accordingly Uni En 10305-3:2016 rule.</i> • <i>Metal drawn rod footrest diameter 11 mm - Fe360</i>
Caratteristiche scocca <i>Shell Specs</i>	<ul style="list-style-type: none"> • Scocca stampata mediante processo di bi-iniezione. Parte anteriore in Polipropilene copolimero, parte posteriore in Polipropilene Copolimero caricato Fibravetro 10%. • <i>Plastic shell manufactured by bi-injection process. Front side in Copolymer Polypropylene, rear side in Copolymer polypropylene 10% loaded by Fibre-glass</i>
Caratteristiche sottosedile <i>Under-set Cover Specs</i>	<ul style="list-style-type: none"> • Polipropilene copolimero. • <i>Copolymer Polypropylene</i>
Piedini <i>Glides</i>	<ul style="list-style-type: none"> • Piedini orientabili con feltro. • <i>Joint glides with felts</i>
Finitura telaio <i>Frame Finishing</i>	<ul style="list-style-type: none"> • Cromo con spessore medio di 10 μ. • <i>Chrome plated with medium thickness 10 micron.</i>

