





FRAME

MANTEINANCE



34,6"



88 cm 34.6"

NUDE LOW TABLE MODULE Designer: Andrés Bluth

88x88x25 cm

**TECHNICAL DATA** 

34,6"x34,6"x9,8"

Av. J.V. Foix 72-74 08034 Barcelona Spain

Tel.: +34 93 205 75 95 info@bivaq.com www.bivaq.com

Extruded aluminum Material

Finish Polyester powder coating

**TABLE TOP** Aluminum plate (polyester powder coating)

Chocolate, white or stone lacquered temperd glass 8mm.

Iroko wood

Dekton porcelain 10mm

HPL Compact 10mm.: Solid phenolic core laminate. HPL and Dekton for its self has supporting capability, resistance to humidity, strength and dimensional stability. Resistant to cigarettes burns, staining, chemicals and abrasion.

**CUSHIONS** Only available with cushion. Removables.

> Material Polyurethane foam Composition 100% polieter fiber

25 Kg/m3 Density

**CUSHIONS FABRIC** Acrylic fabric: 100% solution dyed acrylic with stain and water Material

repellent finish. Washable at 30° C., open air drying.

Vinytex fabric: synthetic fabric made of plastic coated polyester.

**UV** resistance Class. 7/8 **Color fastness** 5 (clasif. máx. 5)

**FABRICS and PAINTING COLORS** Fabrics More than 30 availables fabrics in our Bivag current catalog.

**COM Fabric** 

Powder coating colors More than 15 availables p. coating colors in our Bivag current catalog.

Powder coating aluminum Dekton, HPL Compact

Clean the surface regularly with warm water and neutral soap. Use a non-abrasive sponge or cloth.

Rinse with plenty of water immediately after cleaning. Iroko wood

Iroko may change color or even crack due to humidity levels and sudden changes in temperature. Iroko undergoes a natural process of oxidation that affects its color, which

turns a silver-grey shade. Iroko furniture is treated with a waterproof

sealant. We recommend treating the wood twice a year:

1. Dampen a rag with soap solution and gently wipe the surface of

the wood. The soap solution will free the surface of dust and

contaminating agents from pollution.

2. Once the soap solution has dried we will proceed to the application of the Cromaprotect water based re-toner. Dampen a sponge with the re-toner and apply onto the surface of the wood you want to treat.

**BOX WEIGHT - VOLUME** 25kg (compact) / 25kg (painted glass) / 22kg (aluminum) / 26kg (iroko) / 28kg (dekton) -0,47m<sup>3</sup>

**OTHERS** Suitable for outddor use. Resistant to weathering and sunlight.

**COUNTRY OF ORIGIN** Designed and manufactured in Barcelona, Spain